



August 14, 2020

To Whom It May Concern;

Crane Composites certifies that our Varietex Sandstone decorative FRP, Sandstone finish .090 (2.3 mm) thickness meets the requirements of ASTM D5319.

STA – Varietex Sandstone, Class A Fire Rated:

Crane Composites certifies that Varietex STA .090" (2.3mm) thickness meets the requirements of ASTM D5319:

Classification Class A - Flame spread 0 to 25, smoke development index of 450 or less per ASTM E 84.
Grade 6: 0.090 in. nominal
Tolerances: Width and Length: + .125 in (3.175mm) up to and including 12 ft.
Squareness: + .125 in (3.175mm)
Thickness: + 10% Camber: + .25 in (6.35mm)

This product will meet or exceed our published test numbers on the technical data sheet.

STC – Varietex Sandstone, Class C Fire Rated:

Crane Composites certifies that Varietex STC .090" (2.3mm) thickness meets the requirements of ASTM D5319:

Classification Class C - Flame spread 200 or less, smoke development index of 450 or less per ASTM E 84.
Grade 6: 0.090 in. nominal
Tolerances: Width and Length: + .125 in (3.175mm) up to and including 12 ft.
Squareness: + .125 in (3.175mm)
Thickness: + 10% Camber: + .25 in (6.35mm)

This product will meet or exceed our published test numbers on the technical data sheet

Please feel free to contact me directly at 815-467-8939 with any additional questions.


Thank you for your inquiry.

Sincerely,

A handwritten signature in black ink that reads "Karen A. Nebe".

Karen A. Nebe
Market Manager
Building Products Market

Crane Composites Inc.
23525 W Eames St.
Channahon, IL 60410

Signature: 
Date: 8/14/2020